


## 4 port POE-4 with mode B power for 10/100 devices







- PoE-World Brand injector
- 4 Port 10/100 Ethernet Injector
  - 4 Shielded RJ-45 LAN
  - 4 Shielded RJ-45 LAN+POE
  - 10/100 data rates
- Size: 115 mm x 45mm x 25mm)
- Wall mount stackable
- 650 ma automatic resettable fuse on each port
- Same voltage to all ports power is equally shared as needed by the devices
- Use with any Ethernet switch
  - PoE or non-PoE switches
- Standard power connector
  - 2.1mm x 5.5mm
- LED status indicator
- Operating Temperature
  - 0 to 65 deg C
- Mode B operation
  - pins 4-5 ( + )
  - pins 7-8 ( **-** )
  - reversing cable available
- Ideal for IP Cameras, VOIP phone, WiFi Access Points
- Select the power supply you need 24 to 56 volts
- Technical Support: poe-world.com
- Power is always on
  - no autonegotiation
  - powers 802.3af / 802.3at devices "passively"
- Use our reversing jumper WS-Cisco for reverse polarity if needed

## **Power Input**

Device Spec	Voltage	Note
Passive 802.3af	48 volts	Please see WT-AT-4 for active 802.3at and 802.3af
Mikrotik, Ubiquiti	24 volts	Up to 60 watts total, or 15 watts per port